

Set up DataSync Agent to share to SAP Hana

Fluorine

You can configure your Perspective DataSync Agent to share data from ServiceNow or Salesforce to an SAP Hana database by changing some additional [configurations in your agent.xml file](#).

Prerequisites

- ⚠ First, you will need to install a [DataSync Agent](#).
- ⚠ You will also need to [create a ServiceNow dynamic share/bulk share](#) or [create a Salesforce dynamic share/bulk share](#).
- ⚠ Make sure to [stop running your DataSync Agent](#) before making any Agent configuration changes.

Procedure

To set up your DataSync Agent to share application data to an SAP Hana database, follow these steps:

1

Add the SAP Hana JDBC driver

Add the **ngdbc.jar** JDBC driver that was created upon installation of SAP Hana to your DataSync Agent's **extlib** directory.

2

Install and configure your DataSync Agent

Follow the steps to install the [DataSync Agent](#) or the [DataSync for Salesforce Agent](#) and make sure that your **agent.xml** file is [configured correctly](#).

3

Access your agent.xml configuration file

Navigate to the directory where you saved your **agent.xml** file when installing your DataSync Agent.

4

Update database directives to point to SAP Hana

Open your **agent.xml** file in a text editing application. Then, locate the **<task>** directive(s) within your **<subscribe>** directive, and update the following database-related directives:

Directive	Value to enter
<database_type>	hana
<database_server>	URL/IP address for your SAP Hana database
<database_port>	Port number for your SAP Hana database
<database_user>	Username used to access your SAP Hana database
<database_password>	Password used to access your SAP Hana database
<database_parms>	characterencoding=UTF-8

5

Add the **<uppercase_columns/>** directive

Within the **<subscribe>** **<task>** directive(s), nest the **<uppercase_columns/>** directive to enforce proper column formatting in SAP Hana.

Your **agent.xml** file should look similar to the example shown below:

```
<?xml version="1.0" encoding="ISO-8859-1" standalone="no"?>
<config>
  <agent>
    <share>
      </share>
    <subscribe>
      <task instances="4">
        <task_name>test_hana2_subscribe</task_name>
        <message_connection password="encrypted:v1OtU71yu8N
/EFIJH85SSBtaIt7qEEfvqiqft9VZyYE=" use_basic_consume="false" user="admin" queue="psp.out.
testhana2">https://lab.perspectium.net</message_connection>
        <instance_connection password="encrypted:v1OtU71yu8N/EFIJH85SSPN9aF0P5
/YViVwPEVFcGW4=" user="admin">https://dev17175.service-now.com</instance_connection>
        <handler>com.perspectium.replicator.sql.SQLSubscriber</handler>
        <decryption_key>The cow jumped over the moon</decryption_key>
        <database_type>hana</database_type>
        <database_server>192.168.0.61</database_server>
        <database_port>39013</database_port>
        <database_user>SYSTEM</database_user>
        <database_password>Perspectium123</database_password>
        <database_parms>characterEncoding=UTF-8</database_parms>
        <database>SystemDB</database>
        <uppercase_columns/>
      </task>
    </subscribe>
    <max_reads_per_connect>4000</max_reads_per_connect>
    <polling_interval>5</polling_interval>
    <skip_message_set_processing/>
  </agent>
</config>
```

6

Save your agent.xml file

Save the changes you made to your **agent.xml** file and close the file.

7

Run your DataSync Agent

After configuring your **agent.xml** file to support replication to your SAP Hana database, [start running your DataSync Agent](#) again.

Similar topics

- [DataSync for ServiceNow manual setup](#)
- [DataSync for ServiceNow Agent](#)
- [Get started with the DataSync for ServiceNow Agent](#)
- [Install the DataSync for ServiceNow Agent](#)
- [Start/stop the DataSync for ServiceNow Agent](#)

Contact Perspectium Support



US: 1 888 620 8880

UK: 44 208 068 5953

support@perspectium.com