

Key Set Processing for DataSync Agent

Key Set Processing is a capability of the **DataSync Agent** which can be enabled when replicating messages from a ServiceNow instance to a database. The Key Set capability optimizes throughput while further ensuring message ordering.

NOTE: It's strongly recommended to enable this capability when replicating from a ServiceNow instance.

This is enabled on a task by task basis by adding the following configuration direction within the `<task>` definition.

```
<task>
    <enable_keyset_processing/>
    ...
    ...
</task>
```

The following directives can be added to the `agent.xml` when enabling the **Key Set Processing**:

Directive	Description	Example
<code><keyset_size></code>	Indicates the number of key set processor that will maintain the connection to the database. NOTE: Overriding the default key set size (8) may reduce overall throughput of message processing.	<code><keyset_size>4</keyset_size></code>
<code><queue_consumer_polling_interval></code>	Indicates the time interval the queue will be consumed. By default, the key set is scheduled to read from the queue every two seconds.	<code><queue_consumer_polling_interval>nn</queue_consumer_polling_interval></code> NOTE: The value nn is in milliseconds.
<code><keyset_read_wait_time></code>	Indicates the time each key set processor will wait when reading from its queue. By default, the wait time is 200 milliseconds.	<code><keyset_read_wait_time>nn</keyset_read_wait_time></code>

Example of the `agent.xml`

```
<?xml version="1.0" encoding="ISO-8859-1" standalone="no"?>
<config>
    <agent>
        <share/>
        <subscribe>
            <task>
                <enable_keyset_processing/>
                <keyset_size>4</keyset_size>
                <queue_consumer_polling_interval>nn</queue_consumer_polling_interval>
                <keyset_read_wait_time>nn</keyset_read_wait_time>
                ...
                ...
            </task>
        </subscribe>
        <max_reads_per_connect>4000</max_reads_per_connect>
        <polling_interval>5</polling_interval>
        <skip_message_set_processing/>
    </agent>
</config>
```

Similar topics

- Advanced DataSync Agent Configurations
- Change data type
- DataSync Agent field type mappings
- Monitoring DataSync Agent logs
- Specify Working Directories for Agent Files

Contact Perspectium Support



US: 1 888 620 8880

UK: 44 208 068 5953

support@perspectium.com