

Open Splunk HTTP Event Collector port to the Perspectium Integration Mesh

Fluorine

To enable your Splunk HTTP Event Collector to listen for data that is being shared from your ServiceNow instance, you will need to open your HTTP Event Collector port to the **Perspectium Integration Mesh**.

Prerequisites

⚠ First, you will need to [create a ServiceNow bulk/dynamic share for Splunk](#).

Procedure

To determine your Splunk HTTP Event Collector port to the Perspectium Integration Mesh, follow these steps:

1

Log into Splunk and navigate to **Settings > Data inputs** from the top left-hand side navigation menu.

2

Click **HTTP Event Collector** under **Type**.

3

On the right-hand side of the screen, click **Global Settings**.

4

In the **HTTP Port Number**, note the port that the Splunk HTTP Event Collector is running on. Have your system administrator verify this port is open and accessible by the Perspectium Integration Mesh.

NOTE: The default port that is set when initially configuring your Splunk HTTP Event Collector is **8088**.

For more information on configuring your HTTP Port Number in Splunk, see [enable HTTP Event Collector](#).

Next steps

[Generate a Splunk Event Collector token](#)

Similar topics

- [DataSync for Splunk](#)
- [Generate a Splunk Event Collector token](#)
- [View your event collections in Splunk](#)
- [Create a ServiceNow bulk/dynamic share for Splunk](#)
- [Open Splunk HTTP Event Collector port to the Perspectium Integration Mesh](#)

Contact Perspectium Support



US: 1 888 620 8880

UK: 44 208 068 5953

support@perspectium.com